



Declaration of Performance: SM-43

Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. *Unique identification code of the product-type:*

Slabs of Natural Stone

2. *Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

Avant Garde Imperial Steps (Sandstone)

3. *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*

Slabs of Natural Stone for flooring and stairs, External Use.

4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

Stonemarket, Oxford Road, Ryton-on-Dunsmore, Coventry, Warwickshire, CV8 3EJ

5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

Not applicable

6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

System 4

7. *In case of the declaration of performance concerning a construction product covered by a harmonised standard:*

BS EN 12058:2015

8. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*

Not applicable



Declaration of Performance: SM-43

Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

9. Declared performance

Essential Characteristics	Performance	Relevant Clause of BS EN 12058:2015
Petrographic	Denomination: Light buff to cream with occasional darker bands fine grained Sandstone from Gaarda, Boondi District of Rajasthan, India	4.2.2
Flexural Strength Expressed as; Lowest Expected Value (LEV), Mean Value and SD	LEV 30.5 MPa	4.2.4 EN12372
	Mean 35.7 MPa	
	SD 2.4	
Slip Resistance	Wet 79	4.2.14 EN 14231
	Dry NPD	
Tactility/Visibility	See description on Brochure/data sheet	4.2.15 (visual)
Frost Resistance Percentage loss over 56 cycles	8%	4.2.10 EN12371
Thermal Shock Resistance	NPD	4.2.11
		EN 14066

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Rory Kendrick

International Stone Sourcing Director

Date: 6th November 2017

Version History: Version 3, November 2017 issued due to change in requirements for DOP structure and change of date of issue.